


SELF LOCKING NUTS

MS21045 HEX - SEGMENTED BEAM


MATERIAL - CARBON / ALLOY STEEL
CORROSION RESISTING STEEL
FINISH - CADMIUM PER QQ-P-416 TYPE II
DRY FILM LUBE PER AS5272
PASSIVATE PER AMS2700



STEEL DASH#	LUBE DASH#	CRES DASH#	THREAD SIZE	A	B	AXIAL STR. LBS/MIN
04	L04	C04	4-40	0.150	0.247	750
06	L06	C06	6-32	0.174	0.309	1130
08	L08	C08	8-32	0.235	0.341	1720
3	L3	C3	10-32	0.229	0.372	2460
4	L4	C4	1/4-28	0.284	0.435	4580
5	L5	C5	5/16-24	0.316	0.497	7390
6	L6	C6	3/8-24	0.394	0.559	11450
7	L7	C7	7/16-20	0.452	0.685	16450
8	L8	C8	1/2-20	0.593	0.747	21110
9	-	-	9/16-18	0.664	0.871	26810
10	-	-	5/8-18	0.749	0.934	34130

MS21046 HEX - SEGMENTED BEAM / ELLIPTICAL

MATERIAL - CORROSION RESISTING STEEL
FINISH - SILVER PLATE PER AMS 2410



DASH#	THREAD SIZE	A	B	AXIAL STR. LBS/MIN
C04	4-40	0.150	0.247	750
C06	6-32	0.174	0.309	1130
C08	8-32	0.235	0.341	1720
C3	10-32	0.229	0.372	2460
C4	1/4-28	0.284	0.435	4580
C5	5/16-24	0.316	0.497	7390
C6	3/8-24	0.394	0.559	11450
